

Drink Holder with LED Lit Base

Features

- Stainless steel housing extends deep for high-end look and functions to hold rubber liner in place
- Rubber liner and tiered form holds drinks securely in place
- LED lit base available in blue, red, green, 3000K warm white, 6300K cool white or VersiColor™ RGB.
- LEDs at the base provide unique color patterns inside and project to the rim
- Added wire strain relief prevents any damage to the light during installation
- Available with or without drainage weep hole
- Blind mount or screw mount options avaliable
- IP66 rated, watertight LED strip

Product Details

Housing	Stainless Steel & Acrylic	
Cutout	3.625" / 4" for blind mount	
Drainage	Weep Hole Drainage	
Rim Diameter	4.54"	
Depth	4" With Drain / 3.8" Without Drain	
LED Color	Blue, Red, Green, 3000K or 6300K	RGB*
Voltage	13.6V DC	
Wattage	1.2W	3.7W
Current	0.09A	0.27A

*In order for the RGB option to function properly, an RGB controller is needed. See controller literature sheet for options and specifications.

Specification Guide

Sample Part #: 81429SS304NN-RGB

Base Part


Drain Hole Option

LED Color

Base Part #	Drain Hole Option	LED Color
81429SS304 - Screw Mount 81430SS304 - Blind Mount	NN - No Drain Hole (custom option) *Leave blank if drain hole is desired	BL - Blue RD - Red GR - Green 3K - 3000K Warm White 6K - 6300K Cool White RGB - Red, Green, Blue NO - Unlit



Product Dimensions





3030 Corporate Grove Dr. • Hudsonville • MI • 49426 Phone: 616-396-1355 • Fax: 616-396-1152 • www.itc-us.com • sales@itc-us.com



Drink Holder Installation Instructions

(Part #'s: 81420, 81421, 81423, 81426, 81427, 81429 & 81430)





Drink Holder

Red (+)

Black (-)

2. If installing a standard drink holder proceed to step 3. If installing

Black (-)

12V DC (+)

a lit drink holder follow the wiring instructions below.

 Determine the installation location and drill a 3-5/8" hole using a hole saw (Note: For part #81427 & 81430 you will need to drill a 4" hole).



3. If installing an adhesive mount drink holder, simply remove the paper backing and press in place. If installing the screw mount cup holder screw down using the provided screws. If installing the blind mount, tighten screws until the tabs flip out. Replace the decorative ring.




Adhesive Mount

Blind Mount







VersiColor RGB Option

Incoming 12V DC Power

Single Color Option

Incoming

