## Storage Door Replacement

## How to Remove Old Style Storage Doors

- Step 1. Remove the door struts.
- Step 2. Remove pop rivets or clips from either side of door.
- Step 3. A. Open the storage door to at least a 60° angle.
  - B. Push and hit the bottom edge with your hand or gently with a rubber mallet.
  - C. Work the door back and forth until it pops out of the hinge.

NOTE: IT IS EASIER TO LOOSEN THE DOOR RAIL AND SLIDE THE DOORS IN, BUT THE METAL SCREW COVER WILL BE DAMAGED AND WILL NEED TO BE REPLACED.

- Step 4. Spray the hinge with a lubricant, such as SLICK, before re-installing the door.
- Step 5. Place the door at the same angle, by hitting and pulling on the rear top edge of the door until the door pops into place.

NOTE: DO NOT USE TOO MUCH FORCE, AS THE RAILS CAN BEND AND THIS MAY CAUSE THE DOOR TO SNAP AS IT OPENS.

Step 6. Reinstall pop rivets or clips on hinge rail.

NOTE: NEW CLIPS CAN BE MADE OUT OF THE TOP DOOR RAIL IF DIFFERENT SIZES ARE NEEDED.

Step 7. Reinstall door struts.

## How to Remove New Style Storage Doors

- Step 1. Remove door struts.
- Step 2. Remove the screws on the both sides of the storage door.
- Step 3. Remove door.
- Step 4. Install new door with screws to hinges.
- Step 5. Install door struts.

60° angle